

# VISION MEASURING MACHINE

This series Vision Measuring Machine is designed especially for large scale repeated measuring. It is with high speed, high efficiency and powerful function. Especially suits for large-amount in section which requires high speed, high efficiency and high precision. It is necessary and important equipment within a busy QC line. In all model uses High precision 00 class granite fixed bridged structure for the bracket, along with high precision work-table, in order to ensure the stability and precision of the machine body as long as the high precision of the measuring. Three axis with Panasonic AC servo motor system, recognized by the whole industry as the most reliable system.

## Key Features:

- The base and upright column adopt high precision of granite to ensure the stability of the mechanism system.
- Z-axis adopts precision linear guide with clump weight and the lens is in even force up and down to ensure the precision.
- The laser locating indicator can rapidly find the measuring position of work pieces.
- 0.7x~4.5x Step Zoom Lens.
- The grating scales that mounted on X-axis and Y-axis can make sure the high locating precision
- Z-axis when mounted with grating scale can measure height of work pieces.
- with measuring software and counting card
- With Renishaw Touch Probe



## HVM-MT SERIES

**This** is a manual type video measuring machine with XYZ travel. It is equipped with high quality CCD, powerful 2D measuring software and computer. The machine can measure various work piece such as electronic components, punching parts, plastic and rubber parts etc. effectively.

### Introduction

This series Vision Measuring Machines is Automatic measurement machine with practice function, to **CNC type** fully automatic measurement a machine with off-line programming, high speed and efficiency function in order to meet different customer's requirements. Our all Vision Measuring Machines are compatible with **RENISHAW** high accuracy touch trigger probe to measure parts in Z-axis or simple-3D measurement. SPC statistic analysis software is a standard configuration for our all VMM.

It allows customers to carry out scientific analysis for the production flow to find error trend in the flow and problems in the operations. In addition, all measurement results may be outputted in popular Microsoft office software, such as MS Excel, MS Word to make customers save results conveniently for working out a quality inspection report or analysing further.

Our VMM Software can output results in image file DXF to the popular CAD software, e.g., Auto CAD, Master CAM etc. to facility customers to copy the results. Vice versa, image files in DXF may also be loaded into Software to compare measurement results visually. The software has learning function, users just have to measure the work piece manually for once, the software with record the measuring process, this can be used for the repeated measuring. Users do not have to write any program and this largely simplifies the measuring process. All the moving stage is controlled by a high speed 32-bit DSP controller in order to ensure a reliable high-speed measurement.

**Registered Office:** UGF-12 Ansal Plaza-1 Chiranjeev Vihar Ghaziabad-201002 (U.P.) INDIA

**Workshop:** Khasra No - 63 Village Bayana, Near Wave City, NH 24, Ghaziabad -201015 (U.P.) INDIA

Phone : +91- 8750305291

Email : [info@hsmleindia.in](mailto:info@hsmleindia.in) / [sales@hsmleindia.com](mailto:sales@hsmleindia.com)

Website : [www.hopesmluckyenterprises.in](http://www.hopesmluckyenterprises.in) / [www.hsmleindia.com](http://www.hsmleindia.com) (Under Construction)

## SPC STATISTIC ANALYSIS SOFTWARE

Our all Vision Measurement Machines are equipped with SPC analysis software to allow customers to analyse the measurement results in order to find the error trend in the production flow and have a chance to find problems in the production process on time to make a correction. This will avoid serious errors and waste in each production stage. The SPC Statistic analysis software provides a series of chart patterns & methods for management, such as Xbar-R, Xbar-S, Xmed-R, R-Rm etc, as well as a number of diagram representation methods, for example, vertical, horizontal, 3-dimension, connection diagram etc to improve quality management considerably.

## BASIC FUNCTION OF THE SOFTWARE

**Basic geometry measurement:** Point, line, circle, arc, ellipse, rectangle and curves. Powerful measurement: Automatically find the best boundary point, automatically measure and identify line, circle and arc, can select the point, line, circle, arcs and ellipse with frame, can collect point. manually through a mouse.

**Combination measurement:** Combine the point, line and circle and calculate the distance, angle and intersection point among points, lines and circles.

**Geometrical error measurement:** Measure the parallelism, perpendicular, inclination, displacement, coaxiality and symmetry.

**Coordinate system setting:** Parallely move, rotate and change the original coordinate or reset the coordinate system. Dimension annotation: It can mark the length, angle, radius and diameter on the drawing window conveniently just like using AUTOCAD software.

**Inspection result output:** The drawings and measuring results can be put out in the format of WORD, EXCEL, DXT.

**Auto focusing function:** It can produce a focusing indicating curve by adjusting Z axis and then judge optimum focus distance position so as to reduce focusing error from operator.

**Enlarge small window function:** It can partly enlarge the vision window through the small window on the lower right corner of software so as to accurately aim at the workpiece.

**CAD window:** Special CAD window has the same idea as three coordinates, which make customer vividly understand the test pieces.

**SPC function:** Data statistics report can be edited freely according to user's measuring requirements. Teaching function: User only need to program the measuring path one time when measuring batch parts and set the number of measuring times to automatically complete the measurement.

(The function is only for CNC type).

## **TECHNICAL SPECIFICATIONS:**

Parameter's	Specification		
Model	HVM-250MT	HVM-300MT	HVM-400MT
X-Travel	250mm	300mm	400mm
Y-Travel	150mm	200mm	300mm
Z-Travel	200mm	200mm	200mm
Operating Mode	All three axis are motorized driven (X,Y,Z)		
Resolution(X/Y)	0.0005mm		
Repeatability	0.002mm		
Accuracy	(3+L/200) μm		
Stage Loadcapacity	30kg		
CCD	1/3" 430,000 pixel Colour	1/3" 410,000 pixel Color	
Optical Magnify Zoom	0.7x-4.5x		
Image Magnification	28x - 180x		
Applicable Environment	Temp.20±5°C Humidity 45-75%		

**Registered Office:** UGF-12 Ansal Plaza-1 Chiranjeev Vihar Ghaziabad-201002 (U.P.) INDIA

**Workshop:** Khasra No - 63 Village Bayana, Near Wave City, NH 24, Ghaziabad -201015 (U.P.) INDIA

Phone : +91- 8750305291

Email : info@hsmleindia.in / sales@hsmleindia.com

Website : www.hopesmluckyenterprises.in / www.hsmleindia.com (Under Construction)