

## COMPUTERISED COMPRESSION TESTING MACHINE

ISO 9001: 2015



## **DESCRIPTION: -**

Compression Testing Machines are used in various industries like construction, rubber, spring manufacturing and similar other industries where the compressive strength of the material is to be tested. Our Compression Testing Machine is equipped with hydraulic loading, available in load capacity from 100kN to 2000kN.

Registered Office: UGF-12 Ansal Plaza-1 Chiranjeev Vihar Ghaziabad-201002 (U.P.) INDIA Workshop: Khasra No - 63 Village Bayana, Near Wave City, NH 24, Ghaziabad -201015 (U.P.) INDIA

Phone: +91- 8750305291

Email: info@hsmleindia.in / sales@hsmleindia.com

Website: www.hopesmluckyenterprises.in / www.hsmleindia.com (Under Construction)

ISO 9001: 2015

The loading is with the hydraulic system and the measurements are using the state of art digital control panel. Test results are displayed on the DRO which can be transferred to the computer for further analysis

## **FEATURES: -**

- Sturdy Lead Frame with precision Hydraulic control
- Precision strain gauge type pressure cell for Load measurement
- Displacement measurement by encoder
- Supports compression transverse test
- Very easy to setup the test with user friendly software
- Testing of various spring designed is possible.
- PC based software for capturing test data parameters like load vs displacement
- Online graphic display for load vs Displacement

## **TECHNICAL SPECIFICATION: -**

Parameter's	Specification				
Model	HFHCT-10-	HFHCT-	HFHCT-40-C	HFHCT-60-C	HFHCT-
	C	20-C			100-C
Maximum Capacity	100	200	400	600	1000
(kN)					
Resolution with	0.005 upto 20	0.01 upto 40	0.02 upto 80	0.03 u <mark>pto 12</mark> 0	0.05 upto 200
electronic system(kN)	0.025 above 20	0.05 above 40	0.1 above 80	0.1 <mark>5 ab</mark> ove 120	0.25 above 200
Table size (mm) LxW	2400 x 250	2400 x 400	2650 x 460	2650 x 500	2650 x 500
Clearance for	0 – 400	0 – 650	0 – 750	0 - 800	0 - 800
compression test (mm)					
Distance between	500 <b>– 2150</b>	650 <b>– 21</b> 50	850 <b>–</b> 2300	850 – 2300	850 – 2300
supports (mm)					
Ram stroke (mm)	100	200		250	
Straining speed at no	0 - 300	0 – 150	0-150	0-100	0-100
load (mm/min.)					
Least count of	0.1				
deflection on DRO					
Power (HP), Voltage	1.5HP, 415V,	2HP, 415V, 3Phase		1.5HP, 415V, 3Phase	
(V), Phase	3Phase				
Standard	Comply with ISO or other standards ISO7500, ISO6892				

Registered Office: UGF-12 Ansal Plaza-1 Chiranjeev Vihar Ghaziabad-201002 (U.P.) INDIA Workshop: Khasra No - 63 Village Bayana, Near Wave City, NH 24, Ghaziabad -201015 (U.P.) INDIA

Phone: +91- 8750305291

Email: info@hsmleindia.in / sales@hsmleindia.com

Website: www.hopesmluckyenterprises.in / www.hsmleindia.com (Under Construction)