

## ROLLING MILLS

HSMLE HRM-6 Rolling Mills is suitable for application for a roll of material like Gold alloys, Silver alloys, Cupro-Nickel, Tombac Bronze, Ferritic Stainless Steel, and other similar material.



### TECHNICAL SPECIFICATION

- Digital Display
- Roll Width- 6 “
- Roll Dia. - 4”
- Sheet width to roll - 50mm
- Sheet thickness to roll - 12 mm
- Motion- Reversible motion of rollers
- Input material- Gold alloys, Silver alloys, Cupro-Nickel, Tombac Bronze, Ferritic Stainless Steel and other similar material.
- Screw down-0.01 mm
- Hardness of roll- suitable as per input material.
- Roll material- suitable as per input material or tool steel (UN ST30402)
- Max roller speed- 10 R.P.M. Per minute

**Registered Office:** UGF-12 Ansal Plaza-1 Chiranjeev Vihar Ghaziabad-201002 (U.P.) INDIA

**Workshop:** Khasra No - 63 Village Bayana, Near Wave City, NH 24, Ghaziabad -201015 (U.P.) INDIA

Phone : +91- 8750305291

Email : [info@hsmleindia.in](mailto:info@hsmleindia.in) / [sales@hsmleindia.com](mailto:sales@hsmleindia.com)

Website : [www.hopesmluckyenterprises.in](http://www.hopesmluckyenterprises.in) / [www.hsmleindia.com](http://www.hsmleindia.com) (Under Construction)