

SURFACE ROUGHNESS TESTER

This instrument is compatible with four standards of the site to measure surface roughness of various machinery processed parts, calculate corresponding and clearly display all measurement parameters. When measuring the roughness of a surface, the sensor is placed on the surface and then uniformly slides along the surface by driving the mechanism with the sharp built-in probe. This roughness cause displacement of the probe which results in change of the inductive amount of induction coils so as to generate the analog signal, which is in proportion to the surface roughness at output end of the phase-sensitive rectifier. The exclusive DSP processes and then outputs the measurement results on LCD



Registered Office: UGF-12 Ansal Plaza-1 Chiranjeev Vihar Ghaziabad-201002 (U.P.) INDIA Workshop: Khasra No - 63 Village Bayana, Near Wave City, NH 24, Ghaziabad -201015 (U.P.) INDIA Phone : +91- 8750305291 Email : info@hsmleindia.in / sales@hsmleindia.com Website : www.hopesmluckyenterprises.in / www.hsmleindia.com (Under Construction)



MODEL	HSRT-6210
Display	4 digits, 10 mm LCD, with blue backlight
Parameters	Ra, Rz, Rq, Rt
Measuring Range	Ra, Rq: 0.005-16.00um/0.020-629.9uinch
	Rz,Rt: 0.020-160.0um/0.780-6299uinch
Accuracy	<u>≤±10%</u>
Fluctuation of display value	Not more than 6%
Sensor	Test Principle: Inductance type
	Radius of Probe Pin: 5um
	Material of Probe Pin: Diamond
	Dynamo-measurement of Probe: 4mN(0.4gf)
	Probe Angle: 90°
	Vertical Radius of Guiding Head: 48mm
Maximum driving stroke	17.5mm/0.7inch
Cutoff length (l)	0.25mm / 0.8mm / 2.5mm (optional)
Evaluation length	5L
Driving speed	sampling length = 0.25mm Vt=0.135mm/s
	sampling length = 0.8mm Vt=0.5mm/s_samplin
	length = 2.5mm Vt=1mm/s returning
	Vt=1mm/s
Profile digital filter	Filtered Profile: RC
	Filtered Profile: PC-RC
	Filtered Profile: Gauss
	Non-Filtered Profile: D-P
Resolution	0.001µm if reading <10µm
	0.01µm if 10µm≤re <mark>ading</mark> <100µm
	0.1µm if readin <mark>g ≥100µ</mark> m
Power Li-ion battery	rechargeable
Operating conditions	Temp. 0-50 @
Size	140x57x48 mm (5.5x2.2x1.9 inch)
Weight	about 420 g

Registered Office: UGF-12 Ansal Plaza-1 Chiranjeev Vihar Ghaziabad-201002 (U.P.) INDIA Workshop: Khasra No - 63 Village Bayana, Near Wave City, NH 24, Ghaziabad -201015 (U.P.) INDIA Phone : +91- 8750305291 Email : info@hsmleindia.in / sales@hsmleindia.com Website : www.hopesmluckyenterprises.in / www.hsmleindia.com (Under Construction)