

Stereo Microscope



DESCRIPTION: -

HSMLE offers Stereo Microscope HSM-A Series with Sharp stereo erect image over a wide field view. It has 45° inclined and 360° rotatable binocular head with locked-in eyepiece. The left ocular tube with dioptre adjustment ±5 dp. The interpupillary distance is between 55-75mm.

FEATURES: -

- Sharp Stereo erect image over a wide field of view.
- 45°inclined head with locked-in eyepiece.
- The left ocular-tube with dioptre adjustment ±5dp
- The interpupillary distance is between 55-75mm.
- Three kinds of 180° rotatable objective for selection:
 - o $1\times/2\times$
 - $o 1 \times /3 \times$
 - $0.2 \times /4 \times$
- Power supply 110V/60HZ or 220V/50HZ.
- A wide range of accessories for selection.
- CE approval.



TECHNICAL SPECIFICATIONS:

Model No.	HSM-12A	HSM-13A	HSM-24A				
Eyepiece	WF10x						
Objective	1x / 2x	1x/3x	2x/4x				
Magnification	10x / 20x	10x/30x	20x/40x				
Field of View	20.0 / 10.0mm	20.0 / 7.0mm	10.0 / 5.0mm				
Working	80mm						
Distance(mm)							
Working Plate	Whi <mark>te / Black working</mark> plate						
Illuminator	Natural illuminator						

OPTICAL DATA: -

Model	Objective Eye		epiece (15X) Eyepie		ece (20X)	Working
No		Magnification	Field of	Magnification	Field of	Distance
	- 64		view		view	
BSM-	1x	15x	15mm	20x	10mm	80mm
12A	2x	30x	7.5mm	40x	5.0mm	
BSM-	1x	15x	15mm	20x	10mm	
13A	3x	45x	5.0mm	60x	3.5mm	
BSM-	2x	30x	7.5mm	40x	5.0mm	
24A	4x	60x	3.8mm	80x	2.5mm	

OPTIONAL ACCESSORIES: Eyepiece - WF15x & wf20x

- Illumination:
 - > 10w ring,
 - fluorescent lamp,
 - ➤ fiber optic illuminator Y & O type
 - Halogen, bulb 6v, 20w
- Dark field attachment and Jewel Tweezers
- Working plate
 - White/ black working plate
 - > Frosted glass working plate