

ISO 9001 : 2015

VICKERS HARDNESS TESTER WITH TOUCH SCREEN





5.6" multiple Functions Touch Screen with Hardness Conversation Functions

DESCRIPTION

High-quality imported components, ensure the new type Micro Hardness Testers working more stable. Protected by the state patent application of the lift & down system, after upgrading, the control system can provide more measuring data, and control more precise. This machine is integrated with optics, mechanics and electricity. It with unbeatable price / performance ratio, widely used in quality inspection and quality control field.

- One time casting aluminum machine body with sturdy structure, modular design and stable working performance
- Load from 10 to 1000g, can extend to 2kgf
- Precise manual analog 10X eyepiece

Registered Office: UGF-12 Ansal Plaza-1 Chiranjeev Vihar Ghaziabad-201002 (U.P.) INDIA **Workshop:** Khasra No - 63 Village Bayana, Near Wave City, NH 24, Ghaziabad -201015 (U.P.) INDIA Phone : +91- 8750305291 Email : info@hsmleindia.in / sales@hsmleindia.com Website : www.hopesmluckyenterprises.in / www.hsmleindia.com (Under Construction)



HSMLE India Corporation

ISO 9001 : 2015

- With hardness conversion function
- Touch screen; LED Cold light source
- Dual optical path, can work with hardness measurement software system (software for optional purchase); Eyepiece and camera path can work at same time
- Standard machine come with Precision screw rod lifting system (Worm gear rod lifting system for optional purchase)

APPLICATION

- Steel, nonferrous metals, tinsel, cemented carbide, sheet metal, metallographic structure.
- Carburization, nitriding and decarburization layer, surface hardening layer, galvanized coating.
- Glass, chip and ceramic material.

MAIN FEATURES:-

- Adopted one time casting aluminum machine body and car painting technology, structure more stable and appearance more decent.
- The independent research and development of lift & down system and positioning system, ensured the accuracy and repeatedly of the testing process.
- The optical system designed by our senior optical engineer not only meet the definition of hardness testing requirements, but also can observe the micro structure of the material, image is very clear.
- According to different visual habits of the operators, the strength of the light source can be adjusted.
 To avoid the visual fatigue for long time operation.
- With Vickers hardness and Knoop hardness testing capabilities. By measuring the indentation diagonal length, the hardness will show on the screen directly, no need to check hardness table.
- Industrial digital touch screen can direct display hardness value, conversion hardness value, testing method, testing force, dwell time, easy for operator to save the data.
- Double optical path design. Both eyepiece and CCD camera path can work at same time. No need switch optical path. Camera can be install inside machine (camera for optional purchase).





Model No.	MVH-1000MT	MVH-1000AT	
Turret	Manual Turret	Automatic Turret	
Testing force	10g (0.098N), 25g (0.245N), 50g (0.49N), 100g (0.98N), 200g (1.96N), 300g (2.94N), 500g (4.9N), 1000g (9.8N) Test force error: ±1.0%		
Hardness scale	HV0.01, HV0.025, HV0.05, HV0.1, HV0.2, HV0.3, HV0.5, HV1		
Loading speed	≤0.05mm/sec		
Indenter	Standard Rectangular pyramid diamond indenter (136°±0.5°)		
Min. measuring unit	0.25µm		
Hardness value rang	5HV-3000HV		
Hardness Value of Reading	Digital LCD Screen		
Eyepiece	10X manual analog eyepiece		
Objective lens	10X (observe), 40X (Measurement)		
Total magnification	100X (For Observation), 400X (For Measurement)		
Loading method	Automatically (Load, dwell and unload the testing force)		
Duration time	1-60s (each step is 1 second)		
Maximum height	90 <mark>mm</mark>		
Throat depth	95mm		
Instrument size and Net weight	405*290*480mm (L×W×H)	40kg	
Packing size and Gross weight	580x345x580mm(LxWxH)	55kg	
Light Source	LED cold light source		
Power Supply	220V + 5%, 50/60 Hz (110V is available)		
X-Y Testing Table	Dim.:100×100 mm, Max. Travel Range: 25×25mm, Moving Resolution Ratio: 0.01mm		
Executed Standard	GB/T4340, ASTM E384 & E92, EN-ISO 6507, JIS B-7734		

TECHNICAL SPECIFICATIONS

STANDARD ACCESSORIES: -


Item Name	Qty	Item Name	Qty
Weights shaft	1 рс	Standard block of hardness	2 pcs
Weights	6 pcs	Spare fuse 2A	2 pcs
10X manual micrometer eyepiece	1 рс	Horizontal adjusting screw	4 pcs
10X objective lens	1 pc	Power line	1 рс
40X objective lens	1 pc	Dust proof cover	1 рс
Vickers diamond indenter	1 рс	Manual Book	1 рс
X-Y Testing Table	1 pc	Certificate of quality	1 рс
Level bubble Note: For avoid potential risks, Will remove level bubble if ship by air, since liquid materials are forbidden by airlines	1 pc	Screwdriver	2 pcs
Flat fixture	1 рс	Warranty Card	1 рс
Sheet specimen fixture	1 рс	Accessory box	1 рс

Registered Office: UGF-12 Ansal Plaza-1 Chiranjeev Vihar Ghaziabad-201002 (U.P.) INDIA Workshop: Khasra No - 63 Village Bayana, Near Wave City, NH 24, Ghaziabad -201015 (U.P.) INDIA Phone : +91- 8750305291 Email : info@hsmleindia.in / sales@hsmleindia.com Website : www.hopesmluckyenterprises.in / www.hsmleindia.com (Under Construction)



ISO 9001 : 2015





Double optical path design. Both eyepiece and CCD camera path can work at same time. No need switch optical path.

FEATURES: -

Precision digital eyepiece (10X) with inbuilt encoder, automatic calculate





LED Cold light source (can be continuous use for 24 hours, no heat generates ensure stable working, servicing life can reach 100,000 hours); Lightness can be adjusted, avoid visual fatigue of operator.

X-Y Testing table of Micro Vickers hardness tester Dim.:100×100 mm, Max. Travel Range: 25×25mm, Moving Resolution Ratio: 0.01mm



Registered Office: UGF-12 Ansal Plaza-1 Chiranjeev Vihar Ghaziabad-201002 (U.P.) INDIA Workshop: Khasra No - 63 Village Bayana, Near Wave City, NH 24, Ghaziabad -201015 (U.P.) INDIA Phone : +91- 8750305291 Email : info@hsmleindia.in / sales@hsmleindia.com Website : www.hopesmluckyenterprises.in / www.hsmleindia.com (Under Construction)